

Załącznik nr 6

HiPath4000 typu A

Adresacja modułów liniowych i abonenckich.

DISP-BCSU:TBL;

ADDRESS : LTG 1 LTU 1 SOURCE GROUP 1 ALARMNO-LTU 0									

ASSIGNED MODULE FCT E W ARM INSERTED HW- MODULE									
PEN	MODULE	TYPE	ID	C	Y	NO	MODULE	STATE INFO	STATUS

1	Q2324-X500	STMI4	1	A	0		Q2324-X500	1 -11 -	READY
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----									
IP ADDRESS : 10. 1.231.250 B-CHANNELS : 60 BCHLCNT : 30									
BLOCK NO : 3 PRERESERVED LINES ASSIGNED : NO									
1. FUNCT : HG3550 2 LINES B-CHANNELS : 60 BCHLCNT : 30									
SECURITY STATUS: 1:[] 2:[] 3:[] 4:[] 5:[] 6:[] 7:[] 8:[]									
(SEE BOTTOM) 9:[] 10:[] 11:[] 12:[] 13:[] 14:[] 15:[] 16:[]									
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----									
2	Q2196-X	DIU-N2	1	A	0		Q2196-X	1 -07 -	READY
3	AVAILABLE				0		AVAILABLE		
4	AVAILABLE				0		AVAILABLE		
5	AVAILABLE				0		AVAILABLE		
6	AVAILABLE				0		AVAILABLE		
7	Q2266-X	LTUCA			0		Q2266-X	1 -14 -	READY
8	AVAILABLE				0		AVAILABLE		
9	AVAILABLE				0		AVAILABLE		
10	AVAILABLE				0		AVAILABLE		
11	AVAILABLE				0		AVAILABLE		
12	AVAILABLE				0		AVAILABLE		
13	Q2196-X	DIU-N2	1	A	0		Q2196-X	1 -07 -	READY
14	Q2196-X	DIU-N2	1	A	0		Q2196-X	1 -07 -	READY

Moduły – liczba obwodów / portów.

DISP-BCSU:STAT;

TOTAL OF THE REFERENCE CONFIGURATION

PARTNO FID TYPE NUMBER			

Q2324-X500	1	STMI4	1 => 2 LINE CIRCUITS / PORTS
Q2196-X	1	DIU-N2	3 => 6 LINE CIRCUITS / PORTS